



TECHNICAL BULLETIN

GREENSOLV CN-1

GRAFFITI REMOVER

1) PRODUCT DESCRIPTION

GREENSOLV CN-1 is an extremely effective graffiti remover for metals (ex: Aluminum, steel, magnesium, copper, galvanized,...), wood, plastics, concrete, masonry, glass and even painted surfaces. **GREENSOLV CN-1** is also excellent to clean almost any type of stain or deposits. It has a very low toxicity and is fully biodegradable; it was developed to replace highly toxic and ozone depleting chemicals (i.e. dichloromethane).

Typical applications:

- **Removing graffiti on metals, wood, concrete, masonry, plastics, glass and painted surfaces;**
- Cleaning paint overspray
- Cleaning permanent markers or other though to remove stains



2) **BENEFITS**

GREENSOLV CN-1 is based on a mixture of polar and non-polar biodegradable solvents. This synergetic composition exhibits excellent cleaning capabilities without using any harmful CFC.

Its main benefits are:

- Very efficient
- 100% Biodegradable
- Safe on all metals (NON-CORROSIVE)
- Compatible with painted surfaces, plastics (Plexiglas), concrete, glass & metals
- Low toxicity
- Orange odor
- Long shelf life
- Very low evaporation rate

3) **PHYSICAL PROPERTIES**

Physical appearance	yellowish liquid
Odor.....	orange
Biodegradability.....	100%
Flash Point (Closed Cup)	>37.8°C (100°F)
Specific Gravity (Water = 1).....	0.95 – 1.05
pH (1% in water)	10 – 11
Solubility in water.....	Partially soluble



4) PROCEDURE

IDEAL EQUIPMENT REQUIREMENTS

- Garden sprayer
- High pressure washer, electric or gas powered
- Brush
- Water

(For remote locations, a second garden sprayer can be used for rinsing)

STEP 1. Apply GREENSOLV CN-1 with a garden sprayer or a rag directly on the graffiti.

STEP 2. Wait 2 to 5 minutes and work the chemical into the graffiti with a rag or a brush.

STEP 3. Use a scrub pad whenever the paint is tough to remove.

STEP 4. Rinse with a pressure washer. Reapply GREENSOV CN-1 if necessary.

Note :

Some coatings and paints may degrade when in contact with **GREENSOLV CN-1**. Perform a spot check prior to using **GREENSOLV CN-1**.



5) PERSONAL PROTECTION

- Protection glasses
- Chemical resistant gloves

6) STORAGE

Store **GRAFFITI REMOVER** at a controlled temperature of 0° C to 30° C (32° F to 86° F). Store in a closed container when not in use. The product will not freeze at 0°C. Keep container dry. The shelf life of the product has been determined to be three (3) years.



7) PACKAGING

FORMAT

Pail (18.9 L)
Drum (205 L)

PACKAGING

Metal pail (5 Gal.)
Metal drum (55 Gal.)

July 2005 (Last revision : July 2005)